



Vustr
EASEL STAND



Accessories Included

Floor & Ceiling Mounting Kit

Colors Available

Black & White 


Features

Wi-Fi Available 


1920x1080 Resolution 

IP54 (Optional) 

Cloud Remote Management 

Available in 32", 43", 55" 

Ruggedized Metal enclosure 

Lacquered Glass Protection (Optional) 



Accessories Included

Floor & Ceiling Mounting Kit

Colors Available

Black & White


Features

Wi-Fi Available 

1920x1080 Resolution 

IP54 (Optional) 

Cloud Remote Management 

Available in 32", 43", 55" 

Ruggedized Metal enclosure 

Lacquered Glass Protection (Optional) 



Accessories Included

Floor & Ceiling Mounting Kit

Colors Available

Black & White


Features

Wi-Fi Available 


1920x1080 Resolution 

IP54 (Optional) 

Cloud Remote Management 

Available in 32", 43", 55" 

Ruggedized Metal enclosure 

Lacquered Glass Protection (Optional) 

Model Name		Vustr 32SM	Vustr 43SM	Vustr 55SM	Vustr 65SM	Vustr 75SM	Vustr 86SM
LCD Panel	Screen Size	32"	43"	55"	65"	75"	86"
	Resolution	1366 x 768	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9
	Brightness	270 cd/m ²	300 cd/m ²	440 nits	390 nits	450 nits	500cd/m ²
	Contrast Ratio	1200:1	1200:1	1200:1	1200:1	1200:1	1200:1
	Viewing Angle	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)
	Backlight Life in Hrs	50,000 Hrs (Min.)	50,000 Hrs (Min.)	50,000 Hrs (Min.)	50,000 Hrs (Min.)	50,000 Hrs (Min.)	30,000 Hrs (Min.)
	Refresh Rate in Hz	50/60	50/60	50/60	50/60	50/60	50/60
I/O Interfaces	DP 1.2 in	NA	NA	NA	NA	NA	2
	DP out	NA	NA	NA	NA	NA	1
	HDMI 1.4	2	2	NA	NA	NA	2
	HDMI 2.0	NA	NA	3	3	3	2
	RS232/RJ45	LAN-RJ45	LAN-RJ45	LAN-RJ45	LAN-RJ45	LAN-RJ45	IN-1/OUT-1
Sound	Built-in Speakers	12Wx2(8Ω)	10Wx2(8Ω)	8Wx2(8Ω)	8Wx2(8Ω)	8Wx2(8Ω)	15Wx2(6Ω)
Power	Input Power	AC 90V to AC 264V	AC 90V to AC 264V	AC 100V to AC 240V	AC 100V to AC 240V	AC 100V to AC 240V	AC 100V to AC 240V
	Power Consumption (Typ.)	50W	65W	138W	138W	200W	550W
	Power Consumption (Standby)	≤ 0.5W	≤ 0.5W	≤ 0.5W	≤ 0.5W	≤ 0.5W	≤ 0.5W
Environmental Conditions	Operating Temperature	5°C~55°C	5°C~55°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C
	Operating Humid.	25%~75% RH	25%~75% RH	10%~80%	10%~80%	10%~80%	10%~80%
Physical Specification	Bezel	Narrow	Narrow	Bezel less	Bezel less	Narrow Bezel	US(T/B/L/R) 12.8mm
	Back cover	Plastic	Plastic	Metal	Metal	Metal	PC+ABS V0
	Wall hanging size(mm)	100x100	200x100	200x100	200x100	200x100	800x400
	Wall hanging screws(mm)	-	-	CSK4*50 mm	CSK4*50 mm	CSK4*50 mm	M8*20
	Net Weight	3.8kg	8.5kg	19kg	19.2kg	19.4kg	68Kg
	VESA Mounting	Yes	Yes	Yes	Yes	Yes	Yes
	Gross Weight	5.7kg	9.2kg	28.4kg	29kg	30.2kg	91kg

*specifications are subject to change.



For More Information



contact@techworksworld.com



techworksworld.com